


## **Model EB 365 Edgebander**





#### Features:

- Touch screen control panel
- Heated in-feed fence
- Glue Pot "Easy Clean" Teflon coated
- Coil Feed
- Pneumatic Guillotine
- Four pneumatic side pressure rollers
- End trimming station, pneumatic angel adjustment,
   2 motors (German made linear guide ways)
- Pneumatic switch to change angle
- Top & bottom milling units tillable to 45 deg
- Fluorescent light inside safety hood
- Feed jog button for easy set up
- Pneumatic shut off gate on glue roller
- Front and rear tape overlap adjustment from control panel
- Telescoping panel support for large size panels
- Heavy duty feed chain with replaceable pads
- 24 month limited warranty

#### **Specifications:**

Panel Thickness: 10-60mm
Minimum Panel Width: 80mm
Edge Thickness: 0.4-3mm
Electrics: 3/60/600V
Feed Motor: 1.5 kW 3HP
End Trim: 2 Motors, .35 kW
Top & Bottom Trim: 2 Motors, .75 kW

- Large 3" diameter dust extraction connection
- Large window in safety hood
- Pneumatic gate to prevent feeding panels to close to one another
- Mechanical digital readouts for all adjustments
- European high frequency motors on end trims and milling units
- Top & bottom scraping units, pneumatic blowers, large diameter tracing wheels
- Box to collect PVC shavings
- Buffing units with cloth wheels to clean glue line
- Emergency stop button on out feed end
- CE approved CSA electrical components
- Air regulator, filter, and lubricator
- Machine length 4070mm, weight 1620kg
- Feed speed 12-20m/min
- Extruded aluminum top pressure beam
- Total power requirement 8kw

Machine Dimensions: 4070 x 900 x 1600mm

160" x 36" x 63"

Weight: 1620 kgs



# **BOSS Working Units**

### **Control Panel**



# Coil Feed, Guillotine, Glue Drive, Side Pressure




#### **End Trim**



**Top & Bottom Milling** 




Scrapers



**Buffers** 



Heated In-feed Fence, Pneumatic Gap Control



**Electrical Control Panel** 



